

219 | Odyssey™ 2000

Synthetic Blend Moly Motor Oil API CI-4 Plus/SL SAE 15W-40

DESCRIPTION:

Odyssey 2000 is a high performance, heavy duty synthetic blend moly motor oil. Odyssey 2000 gives multigrade performance for all seasons and all temperatures. It meets and exceeds CI-4 Plus/SL API performance category for both heavy duty diesel as well as gasoline engines. Odyssey 2000 is a high TBN oil which meets and exceeds most engine manufacturers' specifications and is highly formulated for superior performance with extended drain intervals.

COMPOSITION:

Odyssey 2000 begins with its special synthetic base stock blend which consists of pure synthetic hydrocarbon base stocks and polymers blended with ultra-pure iso-dewaxed and severely hydrocracked base stocks which are refined to an exceptionally high viscosity index. Odyssey 2000 is fully compatible with all other synthetic and conventional mineral oil based motor oils.

Odyssey 2000 is formulated as an extended drain motor oil with its superior additive package. Extensive performance testing has proven exceptional deposit control, thermal stability and elimination of most wear, making much longer drain intervals possible. Highly efficient detergent alkalinity provides longer TBN retention while super engine cleanliness spells a dramatic reduction in total maintenance. The superior oxidation and thermal stability of Odyssey 2000, with its highly shear stable viscosity index improves, prevents oil breakdown, making much longer drain intervals possible. Dramatically reduced oil consumption and increased fuel economy can also be attributed to the use of this high performance product. Wear is essentially eliminated with the addition of our exclusive oil soluble friction modifier, Moly-D.

PERFORMANCE CHARACTERISTICS:

Meets and exceeds the following performance categories and specifications:

API CI-4 Plus/SL	JASO DH-1
Allison Transmission C-4	ACEA E5
CAT ECF-1/TO-2 Transmission	CES
Cummins	DC 228.3
Detroit Diesel 93K2124	Scania
Mack EO-N Premium Plus	Volvo

USES:

Odyssey 2000 is recommended for use in many diesel and gasoline engines operated in light to heavy duty service. It is particularly recommended for use in high performance, heavy duty supercharged diesel engines burning both low and high sulfur distillate fuels.



PRIMROSE PLUS

219 Odyssey™ 2000 Synthetic Blend Moly Motor Oil, API CI-4 Plus/SL SAE 15W-40

APPLICATIONS:

- Trucks
- Buses
- Hoists and Cranes
- Compressor Drives
- Cotton Pickers
- Bulldozers
- Automobiles
- Tractors
- Drilling Rig Engines
- Stationary Generators
- Highway Equipment
- Pavers
- Irrigation Engines
- Drag Lines
- Combines

TYPICAL SPECIFICATIONS:

Product No.	219
SAE Grade	15W-40
Viscosity, cSt @ 100°C	15
Viscosity Index	129
Flash Point, °F	465
API Gravity	28.4
Sulfated Ash, % wt	1.45
Total Base Number (TBN)	11